

## 6300 - 6312

Lager Nr.	Abmessungen (mm)				Tragzahlen (kN)		Drehzahlen (r/min)		Gewicht (g)
	d	D	B	rs min	Dyn. Cr	Stat. Cor	Oel	Schmierfett	
6300	10	35	11	0,6	7,65	3,48	24000	18000	53
6301	12	37	12	1,0	9,72	5,08	22000	17000	57
6302	15	42	13	1,0	11,50	5,42	20000	16000	80
6303	17	47	14	1,0	13,50	6,58	19000	15000	109
6304	20	52	15	1,1	15,80	7,88	17000	13000	142
6305	25	62	17	1,1	22,20	11,50	14000	10000	219
6306	30	72	19	1,1	27,00	15,20	12000	9000	349
6307	35	80	21	1,5	33,20	19,20	10000	8000	455
6308	40	90	23	1,5	40,80	24,00	9000	7000	639
6309	45	100	25	1,5	52,70	31,50	6700	8000	830
6310	50	110	27	2,0	61,80	38,00	7500	6300	1050
6311	55	120	29	2,0	72,50	45,00	6700	5600	1350
6312	60	130	31	2,0	58,2	52,00	6500	5300	1700

### Ausführungsarten

- offen ohne Abdichtung = **6xxx**
- einfache abgedichtet = **6xxx 2Z**
- doppelt abgedichtet = **6xxx 2RS**
- in VA doppelt abgedichtet = **S 6xxx**

